

Retracement and Dependent Resurvey
of the Willamette Meridian, through T. 25.S.

CHAINS

$\frac{1}{4}$ S24 |
1927

from which

A madrona, 8 ins. diam., bears ^NS.64*W., 7 lks.
dist., marked $\frac{1}{4}$ S 24 B T.

A fir, 26 ins. diam., bears N.45*W., 100 lks.
dist., marked $\frac{1}{4}$ S 24 B T.

Thence

N.0*43*W.

Asc. 300 ft. over rocky SW. slope.

16.00 Spur, slopes W.; desc. 100 ft. over NW. slope.

21.00 Dry ravine, course W.; asc. 275 ft. over SW. slope.

30.00 Continue asc. along W. slope.

37.99 Point of intersection of line bet. secs. 18 and 19,
determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins., in
the ground, for closing cor. of secs. 18 and 19, with
brass cap marked

T25S	T25S
	S18
R1W	—CC
	S19
S24	R1E
	1927

from which

A fir, 8 ins. diam., bears N.61*E., 46 lks.
dist., marked T 25 S R 1 E S 18 CC B T.

A fir, 8 ins. diam., bears S.40*E., 42 lks.
dist., marked T 25 S R 1 E S 19 C C B T.

40.26 The cor. established for secs. 13, 18, 19 and 24, which
is a basalt stone, 6x10x8 ins. above ground, firmly
set, marked with 3 notches on N. and S. edges; from
which

A fir, 60 ins. diam., bears N.32*E., 72 lks.
dist., old B.T., the marks on which I now destroy.

A cedar, 18 ins. diam., bears S.31*E., 33 lks.
dist., old B.T., the marks on which I now destroy.