

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of Willamette Meridian, through T. 25 S.

CHAINS
40.20

The $\frac{1}{4}$ sec. cor., established for secs. 13 and 18, which is a basalt stone, 6x10x10 ins. above ground, firmly set, marked $\frac{1}{4}$ on W. face.

I now change this cor. to refer to sec. 13 only.

Re-mark the stone $\frac{1}{4}$ S 13 on W. face; from which

A fir, 30 ins. diam., bears S.17*E., 19 lks.

dist., old B.T., the marks on which I now destroy.

A fir, 48 ins. diam., bears S.27*W., 31 lks.

dist., old B.T. with marks grown over.

A cedar, 12 ins. diam., bears N.42*W., 18 lks.

dist., marked $\frac{1}{4}$ S 13 B T. (new B.T.)

Thence

N.0*58'W.

Asc. 90 ft. over SW. slope.

5.00 Spur, slopes W.; desc. 375 ft. over NW. slope.

18.50 Creek, 2 lks. wide, course W.; asc. 400 ft. over SW. slope.

37.43 Point of intersection of line bet. secs. 7 and 18, determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 7 and 18, with brass cap marked

| | |
|------|------|
| T25S | T25S |
| RIW | S7 |
| S13 | CC |
| | S18 |
| | R1E |
| | 1927 |

from which

A fir, 30 ins. diam., bears N.24*E., 137 lks.

dist., marked T 25 S R 1 E S 7 C C B T.

A fir, 16 ins. diam., bears S.37 $\frac{1}{2}$ *E., 151 lks.

dist., marked T 25 S R 1 E S 18 C C B T.

37.45 The witness cor. on the S. side of bluffs, established for secs. 7, 12, 13 and 18, which is a basalt stone, 6x12x6 ins. above ground, firmly set, marked W C on NE. face, with 2 notches on N., and 4 notches on S.