

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey

of the Willamette Meridian, through T. 25 S.

CHAINS

edges.

I now change this cor. to refer to secs. 12 and 13 only.

Re-mark the stone W C S 12 on NW., and S 13 on SW. face;
from which

A fir, 20 ins. diam., bears N.58*E., 20 lks.

dist., old B.T., the marks on which I now destroy.

A fir, 30 ins. diam., bears S.24*W., 48 lks.

dist., marked W C T 25 S R 1 W S 13 B T. (new B.T.)

A fir, 40 ins. diam., bears N.89*W., 20 lks.

dist., old B.T. with marks grown over.

Thence

N.0*28'W.

Across impassable bluffs.

2.46 The point for the cor. of secs. 12 and 13 only falls on
the face of bluffs.

Land, mountainous.

Soil, rocky loam; 3rd and 4th rate.

Timber, fir, hemlock, pine, and cedar.

Undergrowth, vine maple, rhododendron, hazel, willow
and manzanita.

N.0*28'W., on a true line, on E. bdy. of sec. 12.

Across impassable bluffs, over spur and creek, to

7.31 The witness cor. on the N. side of canyon, established
for secs. 7, 12, 13 and 18, which is a basalt stone,
6x12x6 ins. above ground, firmly set, marked W C on
NE. face, with 2 notches on N., and 4 notches on S. edges.

I now change this cor. to refer to secs. 12 and 13, only.

Re-mark the stone W C S 13 on SW., and S 12 on NW. face;
from which

A fir, 16 ins. diam., bears S.74*E., 16 lks.

dist., old B.T., the marks on which I now destroy.

A fir, 14 ins. diam., bears S.38*W., 21 lks.

dist., marked W C T 25 S R 1 W S 12 B T. (new B.T.)