

Retracement and Dependent Resurvey
of the Willamette Meridian, through T. 25 S.

CHAINS	
	A fir, 16 ins. diam., bears N.10*W., 45 lks. dist., old B.T. with marks grown over.
	Thence
	N.0*07*W.
	Asc. 575 ft. to $\frac{1}{4}$ sec. cor., over SE. slope, through heavy timber and dense undergrowth.
2.25	Continue asc. along E. slope.
9.05	Creek, 2 lks. wide, course SE.; continue asc. over SW. slope.
13.25	Same creek, 2 lks. wide, course SW.; continue asc. along E. slope.
20.25	Same creek, 1 lk. wide, course SE.; continue asc. over SW. slope.
30.40	Mid point bet. closing cors., determined as hereinafter set forth.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 7 only, with brass cap marked
	$\begin{array}{c} \\ \frac{1}{4} \text{ S7} \\ \\ 1927 \end{array}$
	from which
	A fir, 24 ins. diam., bears N.49*E., 71 lks. dist., marked $\frac{1}{4}$ S 7 B T.
	A fir, 50 ins. diam., bears S.51*E., 65 lks. dist., marked $\frac{1}{4}$ S 7 B T.
32.62	The $\frac{1}{4}$ sec. cor. established for secs. 7 and 12, which is a basalt stone, 6x10x8 ins., firmly set, marked $\frac{1}{4}$ on W. face.
	I now change this cor. to refer to sec. 12 only.
	Re-mark the stone $\frac{1}{4}$ S 12 on W. face; from which,
	A fir, 36 ins. diam., bears N.63*E., 18 lks. dist., old B.T., the marks on which I now destroy.
	A fir, 30 ins. diam., bears S.21*W., 60 lks. dist., marked $\frac{1}{4}$ S 12 B T. (new B.T.)
	A fir, 16 ins. diam., bears N.49*W., 53 lks.