

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey.
of the Willamette Meridian, through T. 25 S.

CHAINS

dist., old B.T. with marks grown over.

Thence

N.0*14'W.

Along W. slope.

5.70 Asc. S. slope.

15.00 Spur, slopes SW.; thence along W. slope.

17.80 Dry ravine, course SW.; asc. S. slope.

18.90 Chilcoot Trail, and Forest Service telephone line, bears
NE. and SW.


24.25 Top of spur ridge, 685 ft. above 1/4 sec. cor., bears
NE. and SW., slopes SW.

Desc. 50 ft. over NW. slope.

27.80 Dry ravine, course W.; asc. 190 ft. over SW. slope.

37.97 Point of intersection of line bet. secs. 6 and 7,
determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for closing cor. of secs. 6 and 7, with
brass cap marked



from which

A fir, 18 ins. diam., bears N.61'E., 10 lks.
dist., marked T 25 S R 1 E S 6 C C B T.

A fir, 24 ins. diam., bears S.17'E., 75 lks.
dist., marked T 25 S R 1 E S 7 C C B T.

40.20 The cor. established for secs 1, 6, 7 and 12, which
is a badly decayed fir post, with marks illegible.

I now change this cor. to refer to secs. 1 and 12 only.

In place of the decayed post

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 1 and 12 only, with
brass cap marked