

## County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey  
of the Willamette Meridian, through T. 25 S.

CHAINS

T25S	T25S
S1	
S12	R1E
R1W	S6
	1927

from which

- A fir, 20 ins. diam., bears N.26\*E., 49 lks.  
dist., old B.T., the marks on which I now destroy.
- A fir, 48 ins. diam., bears S.54\*E., 30 lks.  
dist., old B.T., the marks on which I now destroy.
- A fir, 60 ins. diam., bears S.48\*W., 29 lks.  
\* dist., old B.T., with marks grown over.
- A fir, 30 ins. diam., bears N.71\*W., 4 lks.  
dist., old B.T., with marks grown over.

This cor. is on a spur, sloping W.

Land, mountainous.

Soil, rocky loam; 2nd and 3rd rate.

Timber, fir, hemlock, pine, cedar, and chinquapin.

Undergrowth, vine maple, rhododendron, hazel, yew and chinquapin.

Thence

N.0\*32'W., on a true line, on E. bdy. of sec. 1.

Desc. 670 ft. over NW. slope, through heavy timber and dense undergrowth.

18.70 Creek, 3 lks. wide, course NW.; continue desc. along W. slope.

32.20 Creek, 10 lks. wide, course W.; asc. 120 ft. over SW. slope.

37.77 40.00 chs. northing from the closing cor. of secs. 6 and 7, determined as hereinafter set forth.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 6 only, with brass cap marked

$\frac{1}{4}$	S6
	1927

from which