

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of South Boundary, T. 24 S., R. 1 E.

CHAINS

The bearing and length of the west half mile is
N.88°59'E., 40.66 chs., and of the east half mile is
N.89°42'E., 40.35 chs.

Thence

East, from the sec. cor., retracing bet. secs. 3 and 34.

40.60 Fall 14 lks. S. of the $\frac{1}{4}$ sec. cor.

81.28 Fall 29 lks. S. of the cor. of secs. 2, 3, 34 and 35.

The bearing and length of the west half mile is
N.89°48'E., 40.60 chs., and of the east half mile is
N.89°47'E., 40.68 chs.

Thence

East, from the sec. cor., retracing bet. secs. 2 and 35.

40.82 Fall 126 lks. S. of the $\frac{1}{4}$ sec. cor.

80.58 Fall 193 lks. S. of the cor. of secs. 1, 2, 35 and 36.

The bearing and length of the west half mile is
N.88°14'E., 40.84 chs., and of the east half mile is
N.89°02'E., 39.77 chs.

Thence

East, from the sec. cor., retracing bet. secs. 1 and 36.

38.84 Fall 39 lks. S. of the $\frac{1}{4}$ sec. cor.

79.14 Fall 96 lks. S. of the cor. of Tps. 24 and 25 S., R. 1 E.
only.

The bearing and length of the west half mile is
N.89°26'E., 38.84 chs., and of the east half mile is
N.89°11'E., 40.30 chs.

Resurvey

The cor. of Tps. 24 and 25 S., R. 1 E., only, is a basalt
stone, 6x10x8 ins. above ground, firmly set, marked

24 S. on N.,
25 S. on S., and
1 E. on W. face; from which

A fir, 24 ins. diam., bears S.15°W., 18 lks.
dist., old B.T. with marks grown over.

A fir, 14 ins. diam., bears N.69°W., 21 lks.
dist., marked T 24 S R 1 E S 36 B T.