

Dependent Resurvey of West Boundary, T. 24 S., R. 2 E.

Chains.

The old cor. of Tps. 24 and 25 S., Rs. 1 and 2 E., is a basalt stone, 6x10x8 ins. above ground, firmly set, marked with 6 grooves on N., E., S., and W. faces; from which

A fir, 24 ins. diam., bears N.49°E., 29 lks.

dist., marked T 24 S R 2 E S 31 B T. (old BT.)

A pine, 24 ins. diam., bears S.63°E., 23 lks.

dist., marked T 25 S R 2 E S 6 B T. (old BT.)

A fir, 24 ins. diam., bears S.15°W., 18 lks.

dist., old BT. with marks grown over.

A fir, 14 ins. diam., bears N.69°W., not N.75°45'W.,

21 lks. dist., marked T 24 S R 1 E S 36 B T. (Old

BT.)

I now change this cor. to refer to Tps. 24 and 25 S., R. 1 E. only, and destroy the marks on the bearing trees in Tps. 24 and 25 S., R. 2 E.

Re-mark the stone

24 S on N.,
25 S on S., and
1 E on W. face.

Thence

N.0°31'E., on a true line, on E. bdy. sec. 36, T. 24 S., R. 1 E.

Asc. 218 ft. over SE. slope, through heavy timber and dense undergrowth.

9.96 Point of intersection of S. bdy. of T. 24 S., R. 2 E., determined as hereinafter set forth.

Set a basalt stone, 20x15x10 ins., 15 ins. in the ground, for closing cor. of Tps. 24 and 25 S., R. 2 E., marked

24 S on N.,
CC and 2 E and 6 grooves on E., and
25 S on S. face;

from which

A fir, 24 ins. diam., bears N.73°E., 82 lks.

dist., marked T 24 S R 2 E S 31 C C B T.