

## Dependent Resurvey of West Boundary, T. 24 S., R. 2 E.

Chains.

A fir, 14 ins. diam., bears S.53°E., 169 lks.  
dist., marked T 25 S R 2 E S 6 C. C B T.

No iron post available for this corner.

-----  
Thence

N.0°31'E., on a true line, on W. bdy. of sec. 31.  
Asc. 55 ft. over SE. slope, through heavy timber and  
dense undergrowth.

3.50 Spur, slopes NE.; desc. 545 ft. over N. slope.

14.90 Dry ravine, course NW.; thence along W. slope.

25.00 Spur, slopes NW.; desc. 35 ft. over N. slope.

29.09 The  $\frac{1}{4}$  sec. cor. established for secs. 31 and 36, which  
is a basalt stone, 6x12x10 ins. above ground, firmly  
set, marked  $\frac{1}{4}$  on W. face; from which

A cedar, 26 ins. diam., bears S.72°E., 30 lks.  
dist., marked  $\frac{1}{4}$  S B T. (old BT.)

A fir, 40 ins. diam., bears S.35°W., 29 lks.  
dist., old BT. with marks grown over.

I now change this cor. to refer to sec. 36 only, and  
destroy the marks on the bearing tree in sec. 31.

Re-mark the stone  $\frac{1}{4}$  S 31 on W. face; from which

A fir, 30 ins. diam., bears N.69°W., 69 lks.  
dist., marked  $\frac{1}{4}$  S 36 B T. (new BT.)

Thence

N.0°05'E., continuing measurement.

Desc. 522 ft. to Cedar Creek, over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor. of sec. 31 only, with  
brass cap marked

$\frac{1}{4}$  S31

1926

from which

A fir, 6 ins. diam., bears N.77°E., 21 lks.  
dist., marked  $\frac{1}{4}$  S 31 B T.