

Retracement and Dependent Resurvey
of South Boundary, T. 24 S., R. 1 E.

CHAINS

Thence

S.89°11'W., on a true line, resurveying S. bdy. of sec. 36.

Asc. SE. slope, through heavy timber and dense undergrowth.

10.00 Spur ridge, bears NE. and SW.; desc. NW. slope.

25.65 Creek, 2 lks. wide, course N.; asc. E. slope.

32.50 Spur, slopes NE.; desc. NW. slope.

40.00 Mid point on N. bdy. of sec. 1, determined as hereinafter set forth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap marked

$\frac{1}{4}$ S1
1928

from which

A fir, 20 ins. diam., bears S.53°E., 34 lks. dist., marked $\frac{1}{4}$ S 1 B T.

A cedar, 6 ins. diam., bears S.48°W., 67 lks. dist., marked $\frac{1}{4}$ S 1 B T.

40.30 The $\frac{1}{4}$ sec. cor. established for secs. 1 and 36, which is a basalt stone, 6x10x8 ins. above ground, firmly set, marked $\frac{1}{4}$ on N. face.

I now change this cor. to refer to sec. 36 only.

Re-mark the stone $\frac{1}{4}$ S 36 on N. face; from which

A fir, 26 ins. diam., bears N.75°E., 24 lks. dist., marked $\frac{1}{4}$ S 36 B T. (New B.T.)

A hemlock, 16 ins. diam., bears S.41°W., 72 lks. dist., old B.T., the marks on which I now destroy.

A fir, 24 ins. diam., bears N.69 $\frac{1}{2}$ °W., 134 lks. dist., marked $\frac{1}{4}$ S 36 B T. (New B.T.)

The old B.T. in sec. 36 is dead.

Thence

S.89°26'W.