

## County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey  
of South Boundary, T. 24 S., R. 1 E.

CHAINS

brass cap marked

T24S R1E	
S35	
S2	S1
T25S	R1E
CC	
1928	

from which

A fir, 16 ins. diam., bears S.63\*E., 55 lks.

dist., marked T 25 S R 1 E S 1 C C B T.

A fir, 18 ins. diam., bears S.26 $\frac{1}{2}$ \*W., 45 lks.

dist., marked T 25 S R 1 E S 2 C C B T.

3.00 Top of spur ridge, bears NW. and SE. Johnson trail,  
bears same.

Leave old burn, enter scattered timber and undergrowth,  
bears NW. and SE.

Along rocky S. slope.

14.00 Leave scattered timber and undergrowth, enter heavy  
timber and undergrowth, bears NE. and SW.

Asc. 190 ft. over SE. slope.

20.30 Spur, slopes S.; desc. 130 ft. over SW. slope.

25.35 Dry ravine, course S.; asc. 170 ft. over SE. slope.

39.77 The  $\frac{1}{4}$  sec. cor. established for secs. 2 and 35, which is  
a basalt stone, 6x10x4 ins. above ground, firmly set,  
marked  $\frac{1}{4}$  on N. face.

I now change this cor. to refer to sec. 35 only.

Re-mark the stone  $\frac{1}{4}$  S 35 on N. face; from which

A madrona, 12 ins. diam., bears N.32\*E., 16 lks.

dist., old B.T. with marks grown over.

A fir, 30 ins. diam., bears S.44\*E., 45 lks. (not 4)

dist., old B.T., the marks on which I now destroy.

A fir, 10 ins. diam., bears N.44\*E., 42 lks.

dist., marked  $\frac{1}{4}$  S 35 B T. (New B.T.)

Thence

S.88\*14'W.

0.96 Mid point on N. bdy. of sec. 2, determined as hereinafter  
set forth.