

## County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey  
of South Boundary, T. 24 S., R. 1 E.

## CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 2 only, with brass cap marked,

$$\frac{1}{4} \text{ S S2}$$

1928

from which.

A fir, 10 ins. diam., bears S.45\*E., 38 lks. dist., marked  $\frac{1}{4}$  S 2 B T.

A fir, 8 ins. diam., bears S.26\*W., 22 lks. dist., marked  $\frac{1}{4}$  S 2 B T.

2.70 Spur, 30 ft. above  $\frac{1}{4}$  sec. cor., slopes SW.; desc. 565 ft. over SW. slope.

14.90 Brook, 1 lk. wide, course SW.

Thence along S. slope.

21.35 Desc. SW. slope.

23.25 Dry ravine, course S.; asc. 40 ft. over SE. slope.

27.85 Desc. 200 ft. over SW. slope.

35.20 Creek, 3 lks. wide, course SE.; asc. 55 ft. over E. slope.

40.80 Brook, 2 lks. wide, course SE.

40.84 The cor. of secs. 2, 3, 34 and 35, which is a basalt stone, firmly set, 6x8x8 ins. above ground, marked with 4 notches on W., and 2 notches on E. edges; from which

A cedar, 16 ins. diam., bears N.75\*E., 36 lks. dist., marked T 24 S R 1 E S 35 B T. (Old B.T.)

A fir, 10 ins. diam., bears S.46 $\frac{1}{2}$ \*E., 35 lks. dist., marked T 25 S R 1 E S 2 B T. (New B.T.)

A fir, 40 ins. diam., bears S.21 $\frac{1}{2}$ \*W., 35 lks. dist., marked T 25 S R 1 E S 3 B T. (Old B.T.)

A cedar, 8 ins. diam., bears N.41\*W., 64 lks. dist., marked T 24 S R 1 E S 34 B T. (Old B.T.)

The original bearing tree in sec. 2 is dead.

Land, mountainous.

Soil, coarse sandy loam, rocky in places; 3rd and 4th rate.