

Retracement and Dependent Resurvey
of South Boundary, T. 24 S., R. 1 E.

CHAINS

Timber, fir, cedar and pine.

Undergrowth, vine maple, rhododendron, hazel, manzanita,
and snow brush.

Thence

S.89°47'W., on a true line, on S. bdy. of sec. 34.

Asc. 435 ft. over general E. slope, through heavy timber
and dense undergrowth.

33.45 Spur, slopes S.; desc. 265 ft. over SW. slope.

34.25 Forest Service way trail, bears N. and S.

40.00 Mid point on N. bdy. of sec. 3, determined as hereinafter
set forth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for $\frac{1}{4}$ sec. cor. of sec. 3 only, with brass cap
marked

$\frac{1}{4}$ S3
1928

from which

A fir, 14 ins. diam., bears S.73°E., 24 lks.
dist., marked $\frac{1}{4}$ S 3 B T.

A fir, 14 ins. diam., bears S.73 $\frac{1}{2}$ °W., 28 lks.
dist., marked $\frac{1}{4}$ S 3 B T.

40.68 The $\frac{1}{4}$ sec. cor. established for secs. 3 and 34, which is
a sandstone, 6x8x6 ins. above ground, firmly set,
marked $\frac{1}{4}$ on N. face.

I now change this cor. to refer to sec. 34 only.

Re-mark the stone $\frac{1}{4}$ S 34 on N. face; from which

A fir, 16 ins. diam., bears North, 12 lks.
dist., old B.T. with marks grown over.

A cedar, 6 ins. diam., bears N.9 $\frac{1}{2}$ °E., 24 lks.
dist., marked $\frac{1}{4}$ S 34 B T. (New B.T.)

A fir, 12 ins. diam., bears S.30°E., 26 (not 16) lks.
dist., old B.T., the marks on which I now destroy.

Thence

S.89°48'W.