

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey  
of South Boundary, T. 24 S., R. 1 E.

CHAINS

0.50 Dry ravine, course SW.; asc. 35 ft. over SE. slope.  
2.85 Along S. slope.  
6.00 Spur, slopes S.; desc. 300 ft. over W. slope.  
18.90 Creek, 10 lks. wide, course SE.; asc. 575 ft. over NE. slope.  
31.30 Continue asc. over SE. slope.  
39.32 Point of intersection of line bet. secs. 3 and 4, determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap marked

T24S R1E  
S34  
-----  
S4 S3  
T25S R1E  
CC  
1928

from which

A fir, 12 ins. diam., bears S.60°E., 23 lks. dist., marked T 25 S R 1 E S 3 C C B T.  
A fir, 14 ins. diam., bears S.10°W., 39 lks. dist., marked T 25 S R 1 E S 4 C C B T.

40.60 The cor. established for secs. 3, 4, 33 and 34, which is a sandstone, 6x12x6 ins. above ground, firmly set, marked with 3 notches on E. and W. edges.

I now change this cor. to refer to secs. 33 and 34 only.

Re-mark the stone,

S34 on NE., and  
S33 on NW. face; from which

A fir, 12 ins. diam., bears N.14°E., 23 lks. dist., old B.T. with marks grown over.  
A fir, 12 ins. diam., bears S.31½°E., 54 lks. dist., old B.T. the marks on which I now destroy.  
A fir, 16 ins. diam., bears S.8°W., 20 lks. dist., old B.T. the marks on which I now destroy.  
A madrona, 14 ins. diam., bears N.41½°W., 45 lks. dist., old B.T. with marks grown over.