

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of South Boundary, T. 24 S., R. 1 E.

CHAINS

A fir, 14 ins. diam., bears N.13*E., 42 lks.
dist., old B.T. with marks grown over.
A fir, 14 ins. diam., bears S.28*W., 28 lks.
dist., old B.T. the marks on which I now destroy.
A fir, 10 ins. diam., bears N.42 $\frac{1}{2}$ *W., 32 lks.
dist., marked $\frac{1}{4}$ S 33 B T. (New B.T.)

Thence

S.88*59*W.

Asc. 170 ft. over NE. slope.

15.00 Spur, slopes SE.; desc. 130 ft. over SW. slope.

21.85 Dry ravine, course S.; asc. 270 ft. over NE. slope.

27.50 Continue asc. along S. slope.

38.68 Point of intersection of line bet. secs. 4 and 5,
determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for closing cor. of secs. 4 and 5, with
brass cap marked

T24S R1E
S33

S5	S4
T25S	R1E
CC	
1928	

from which

A fir, 16 ins. diam., bears S.48*E., 86 lks.
dist., marked T 25 S R 1 E S 4 C C B T.

A fir, 20 ins. diam., bears S.15*W., 55 lks.
dist., marked T 25 S R 1 E S 5 C C B T.

40.66 The cor. established for secs. 4, 5, 32 and 33, which
is a basalt stone, 6x12x8 ins. above ground, firmly
set, marked with 2 notches on W., and 4 notches on
E. edges.

I now change this cor. to refer to secs. 32 and 33 only.

Re-mark the stone

S33 on NE., and

S 32 on NW. face; from which.

A hemlock, 10 ins. diam., bears N.27*E., 18 lks.