

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of South Boundary, T. 24 S., R. 1 E.

CHAINS

dist., old B.T. with marks grown over.

A fir, 16 ins. diam., bears S.81°E., 43 lks.

dist., old B.T. the marks on which I now destroy.

A fir, 30 ins. diam., bears S.57°W., 23 lks.

dist., old B.T. the marks on which I now destroy.

A fir, 16 ins. diam., bears N.34°W., 34 lks.

dist., old B.T. with marks grown over.

Land, mountainous.

Soil, coarse rocky loam; 2nd and 3rd rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, vine maple, rhododendron, hazel and oak.

Thence

S.89°00'W., on a true line, on S. bdy. of sec. 32.

Asc. 65 ft. over SE. slope, through heavy timber and dense undergrowth.

7.20 Spur, slopes SE.; desc. 220 ft. over SW. slope.

22.00 Creek, 1 lk. wide, course SE.; asc. 305 ft. over E. slope.

35.00 Spur, slopes SE.; desc. SW. slope.

38.00 Asc. NE. slope.

38.05 Mid point on N. bdy. of sec. 5, determined as hereinafter set forth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 5 only, with brass cap marked

$\frac{1}{4}$ S5
1928

from which

A fir, 8 ins. diam., bears S.25 $\frac{1}{2}$ °E., 76 lks.

dist., marked $\frac{1}{4}$ S 5 B T.

A fir, 8 ins. diam., bears S.12 $\frac{3}{4}$ °W., 82 lks.

dist., marked $\frac{1}{4}$ S 5 B T.

40.09 The $\frac{1}{4}$ sec. cor., established for secs. 5 and 32, which is