

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of South Boundary, T. 24 S., R. 1 E.

CHAINS

a basalt stone, 6x12x4 ins. above ground, firmly set,
marked $\frac{1}{4}$ on N. face.

I now change this cor. to refer to sec. 32 only.

Re-mark the stone $\frac{1}{4}$ S 32 on N. face; from which

A fir, 14 ins. diam., bears N.80*E., 22 lks.
dist., marked $\frac{1}{4}$ S 32 B T. (New B.T.)

A fir, 30 ins. diam., bears N.42*W., 15 lks.
dist., old B.T. with marks grown over.

The old B.T. in sec. 5 is dead.

Thence

S.88*45'W.

Asc. along S. slope.

13.00 Bluff, 30 ft. high, faces E.

14.20 Top of spur ridge, bears NE. and SW., slopes SW.
Desc. 520 ft. over NW. slope.


16.10 Forest Service trail, bears NE. and SW.

31.10 Creek, 2 lks. wide, course NW.; asc. 110 ft. over NE.
slope.

37.00 Spur, slopes N.; desc. NW. slope.

37.99 Point of intersection of line bet. secs. 5 and 6,
determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for closing cor. of secs. 5 and 6, with
brass cap marked



from which

A fir, 8 ins. diam., bears S.25*E., 30 lks.
dist., marked T 25 S R 1 E S 5 C C B T.

A fir, 10 ins. diam., bears S.7*W., 32 lks.
dist., marked T 25 S R 1 E S 6 C C B T.

38.83 The cor. established for secs. 5, 6, 31 and 32, which
is a basalt stone, 6x16x8 ins. above ground, firmly set,
marked with 1 notch on W., and 5 notches on E. edges;