

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of South Boundary, T. 24 S., R. 1 E.

CHAINS
39.80

The $\frac{1}{4}$ sec. cor. established for secs. 6 and 31, which is a basalt stone, 6x8x5 ins. above ground, firmly set, marked $\frac{1}{4}$ on N. face.

I now change this cor. to refer to sec. 31 only.

Re-mark the stone $\frac{1}{4}$ S31 on N. face; from which

A fir, 10 ins. diam., bears N.15*E., 32 lks. dist., marked $\frac{1}{4}$ S 31 B T. (New B.T.)

A fir, 20 ins. diam., bears S.10*W., 19 lks. dist., old B.T. the marks on which I now destroy.

A fir, 14 ins. diam., bears N.30*W., 10 lks. dist., old B.T. with marks grown over.

Thence

S.89*43'W.

Asc. 40 ft. over E. slope to

2.20 Spur, slopes N. Chilcoot lookout bears S., 10 chs. dist.

Desc. 1300 ft. over W. slope.

36.20 Brook, 2 lks. wide, course N.; asc. 25 ft. over NE. slope.

37.78 The cor. of Tps. 24 and 25 S., Rs. 1 E. and 1 W., hereinbefore described.

Land, mountainous.

Soil, coarse rocky loam; 2nd, 3rd and 4th rate.

Timber, fir, cedar and pine.

Undergrowth, vine maple, rhododendron, hazel and manzanita.

South Boundary of T. 25 S., R. 1 E.

From the cor. of Tps. 25 S., Rs. 1 E. and 1 W., only, East, on a random line for distance only, along the S. bdy. of T. 25 S., R. 1 E., setting temp. $\frac{1}{4}$ sec. cors. and sec. cors. at intervals of 40.00 chs., and at

477.27 Intersect line projected south, from the cor. of Tps. 24 and 25 S., R. 1 E., only.

At the point of intersection