

South Boundary of T. 25 S., R. 1 E.

CHAINS

A fir, 6 ins. diam., for cor. of Tps. 25 S., Rs. 1 and 2 E., I mark

T 25 S R 1 E S 36 on NW., and
R 2 E S 31 on NE. side; from which

A fir, 12 ins. diam., bears N. 51° *E., 70 lks. dist., marked T 25 S R 2 E S 31 B T.

A hemlock, 15 ins. diam., bears N. 61° *W., 8 lks. dist., marked T 25 S R 1 E S 36 B T.

Thence

West, on a true line, on S. bdy. of sec. 36.

Asc. 120 ft. over E. slope, through heavy timber and dense undergrowth.

7.25 Top of spur ridge, bears N. and S.; desc. 1150 ft. to $\frac{1}{4}$ sec. cor. along top of rocky spur, slopes W.

19.75 Top of bluff, 110 ft. high, faces SW. Continue desc. over rock slide.

24.50 Leave rock slide, bears NE. and SW.; continue desc. along S. slope.

28.75 Spur, slopes SW.; continue desc. over steep W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap marked

$\frac{1}{4}$ S36
1927

from which

A fir, 12 ins. diam., bears N. 34° *E., 38 lks. dist., marked $\frac{1}{4}$ S 36 B T.

A fir, 22 ins. diam., bears N. 77° *W., 40 lks. dist., marked $\frac{1}{4}$ S 36 B T.

Continue desc. over SW. slope, 250 ft. to

47.85 Deep Creek, 5 lks. wide, course NW.; asc. 400 ft. over NE. slope.

62.50 Spur, slopes N.; desc. 340 ft. along N. slope.

68.00 Bluff, 40 ft. high, faces W.; continue desc. over steep W. slope.

73.50 Creek, 5 lks. wide, course N.