

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 25 S., R. 1 E.

CHAINS	Continue asc. over NE. slope.
45.25	Spring branch, 1 lk. wide, course NE.; asc. E. slope.
51.75	Spur, 125 ft. above $\frac{1}{4}$ sec. cor., slopes NE.; desc. 50 ft. along N. slope.
59.25	Creek, 4 lks. wide, course NE.; asc. 300 ft. over E. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 34 and 35 only, with brass cap marked

T25S	R1E
S34	S35
1927	

from which

A fir, 18 ins. diam., bears N.28*E., 19 lks. dist., marked T 25 S R 1 E S 35 B T.

A fir, 15 ins. diam., bears N.52*W., 40 lks. dist., marked T 25 S R 1 E S 34 B T.

Land, mountainous.

Soil, coarse rocky loam; 2nd and 3rd rate.

Timber, fir, hemlock and cedar.

Undergrowth, vine maple, rhododendron, hazel and huckleberry.

West, on S. bdy. of sec. 34.

Asc. 190 ft. over SE. slope, through heavy timber and dense undergrowth.

12.00 Spur, slopes NE.; desc. 340 ft. over NW. slope.

15.85 Bluff, 75 ft. high, faces W.

23.60 Bluff, 50 ft. high, faces SW.

24.50 Dry ravine, course NW.; asc. 45 ft. over rocky NE. slope.

31.25 Spur, slopes N.; desc. 205 ft. over NW. slope.

37.25 Dry ravine, course NW.; asc. 60 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 34 only, with brass cap marked

$\frac{1}{4}$ S34
1927