

## County Surveyor's Record, Douglas County, Oregon

## South Boundary of T. 25 S., R. 1 E.

CHAINS					
	N. slope.				
12.00	Desc. 20 ft. over NW. slope.				
15.00	Dry ravine, course NW.; asc. 105 ft. over NE. slope.				
20.70	Spur, slopes N.; desc. 400 ft. over NW. slope.				
37.25	Dry ravine, course SW.; continue desc. along S. slope.				
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 33 only, with brass cap marked <div style="text-align: center;"> <u><math>\frac{1}{4}</math> S33</u>  1927  from which  A fir, 38 ins. diam., bears N.34*E., 64 lks. dist., marked <math>\frac{1}{4}</math> S 33 B T.  A fir, 18 ins. diam., bears N.65*W., 44 lks. dist., marked <math>\frac{1}{4}</math> S 33 B T.  Desc. 320 ft. over SW. slope. </div>				
47.35	Creek, 1 lk. wide, course NW.; continue desc. over NW. slope.				
56.80	Creek, 1 lk. wide, course N.; asc. 40 ft. over E. slope.				
58.50	Spur, slopes N.; desc. 15 ft. to				
59.25	Asc. 185 ft. along broken N. slope.				
65.60	Brook, 1 lk. wide, course N.; continue asc. over NE. slope.				
78.35	Spur, slopes N.; desc. 50 ft. over NW. slope.				
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 32 and 33 only, with brass cap marked <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T25S</td> <td>R1E</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> </table> 1927  from which  A fir, 6 ins. diam., bears N.25*E., 13 lks. dist., marked T 25 S R 1 E S 33 B T.  A fir, 6 ins. diam., bears N.33*W., 16 lks. dist., marked T 25 S R 1 E S 32 B T.  Land, mountainous.  Soil, coarse rocky loam; 2nd and 3rd rate. </div>	T25S	R1E	S32	S33
T25S	R1E				
S32	S33				