

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 25 S., R. 1 E.

CHAINS

bears NW. and SE.

45.95 Canton Creek, 100 lks. wide, course SE.; asc. 680 ft. over NE. slope.

76.85 Dry ravine, course NE.

77.27 The cor. of Tps. 25 S., R. 1 E. and 1 W. only, hereinbefore described.

Land, mountainous.

Soil, coarse rocky loam; 2nd and 3rd rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, vine maple, rhododendron and hazel.

East Boundary of T. 25 S., R. 1 E.

From the cor. of Tps. 24 and 25 S., R. 1 E., only, South, on a random line, for distance only, on E. bdy. of T. 25 S., R 1 E., setting temp. $\frac{1}{4}$ sec. cors. and sec. cors. at intervals of 40.00 chs., and at

489.04 Intersect line projected East from the cor. of Tps. 25 S.; Rs. 1 E. and 1W., only.

At the point of intersection set the cor. of Tps. 25 S., Rs. 1 and 2 E., only, hereinbefore described.

Thence

North, on a true line, bet. secs. 31 and 36.

Asc. 85 ft. along E. slope, through heavy timber and dense undergrowth.

15.00 Spur, slopes E.; desc. 290 ft. over broken NE. slope.

37.20 Spring branch, 1 lk. wide, course E.; continue desc. over NE. slope, 25 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S36 | S31
1927

from which

A pine, 15 ins. diam., bears N.51*E., 51 lks. dist., marked $\frac{1}{4}$ S 31 B T.