

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 25 S., R. 1 E.

CHAINS

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
 S25 | S30  
 1927

from which

A fir, 12 ins. diam., bears S.41\*E., 39 lks. dist., marked  $\frac{1}{4}$  S 30 B T.

A hemlock, 12 ins. diam., bears S.27\*W., 32 lks. dist., marked  $\frac{1}{4}$  S 25 B T.

Continue desc. over NE. slope, 110 ft. to

45.20 Singe Creek, 10 lks. wide, course W.; asc. 130 ft. along W. slope.

52.20 Creek, 2 lks. wide, course SW.; asc. 480 ft. over SW. slope.

65.70 Continue asc. over S. slope.

74.50 Top of spur ridge, bears E. and W., slopes W. Descend 225 ft. over steep N. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 19, 24, 25 and 30, with brass cap marked

T25S  
 R1E | R2E  
 S24 | S19  
 S25 | S30  
 1927

from which

A fir, 36 ins. diam., bears N.51\*E., 48 lks. dist., marked T 25 S R 2 E S 19 B T.

A fir, 36 ins. diam., bears S.70\*E., 38 lks. dist., marked T 25 S R 2 E S 30 B T.

A hemlock, 28 ins. diam., bears S.30\*W., 50 lks. dist., marked T 25 S R 1 E S 25 B T.

A fir, 50 ins. diam., bears N.73\*W., 102 lks. dist., marked T 25 S R 1 E S 24 B T.

Land, mountainous.

Soil, coarse rocky loam; 2nd and 3rd rate.