

East Boundary of T. 25 S., R. 1 E.

CHAINS

Timber, fir, hemlock, pine and cedar.
Undergrowth, vine maple, rhododendron, huckleberry and hazel.

North, bet. secs. 19 and 24.

Desc. 325 ft. over steep N. slope, through heavy timber and dense undergrowth.

2.25 Continue desc. over steep NW. slope.

7.25 Creek, 1 lk. wide, course N.75*W.; asc. 45 ft. along broken W. slope.

10.25 Desc. 125 ft. along broken W. slope.

23.00 Dry ravine, course W.

24.50 Spur, slopes W.; desc. 320 ft. over steep NW. slope.

26.70 Bluff, 50 ft. high, faces NW.

30.00 Steamboat Creek, 3 chs. wide, course SW., from N.5*E. Thence across flat.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S24 | S19
1927

from which

A cedar, 12 ins. diam., bears S.16*E., 14 lks. dist., marked $\frac{1}{4}$ S 19 B T.

A fir, 16 ins. diam., bears S.26*W., 18 lks. dist., marked $\frac{1}{4}$ S 24 B T.

49.15 Steamboat Trail and Forest Service telephone line, bears N.5*E., and SW.

Asc. 370 ft. along rocky E. slope.

58.00 Continue asc. over SE. slope.

73.40 Spur, slopes E.; desc. 185 ft. over NE. slope.

79.00 Creek, 3 lks. wide, course E.; asc. 30 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, with brass cap marked