

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 25 S., R. 1 E.

CHAINS	
3.30	Creek, 1 lk. wide, course SE.; asc. 475 ft. over SW. slope.
9.00	Dry draw, opens SW.
14.00	Continue asc. over SE. slope.
19.00	Continue asc. along E. slope.
29.15	Johnson trail, bears NE. and SW.
30.50	Spur, slopes NE.; desc. 200 ft. over NW. slope.
36.00	Spring branch, 1 lk. wide, course NE.; thence along E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked $\begin{array}{c} \frac{1}{4} \\ S12 S7 \\ 1928 \end{array}$
	from which
	A fir, 16 ins. diam., bears N.35*E., 34 lks. dist., marked $\frac{1}{4}$ S 7 B T.
	A fir, 12 ins. diam., bears N.75*W., 5 lks. dist., marked $\frac{1}{4}$ S 12 B T.
	Desc. 490 ft. over NE. slope.
63.80	Creek, 1 lk. wide, course NE.
66.50	Johnson Creek, 10 lks. wide, course SE.; asc. 265 ft. over SE. slope.
78.40	Spur, slopes E.; desc. 30 ft. over NE. slope.
80.00	Set an iron post, 3 ft. long, 2 in. diam., 27 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, with brass cap marked $\begin{array}{c} T25S \\ R1E R2E \\ \hline S1 S6 \\ S12 S7 \\ 1928 \end{array}$
	from which
	A cedar, 23 ins. diam., bears N.82*E., 57 lks. dist., marked T 25 S R 2 E S 6 B T.
	A fir, 38 ins. diam., bears S.69 $\frac{1}{2}$ *E., 182 lks. dist., marked T 25 S R 2 E S 7 B T.
	A fir, 52 ins. diam., bears S.72*W., 129 lks.