

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 25 S., R. 1 E.

CHAINS

Desc. 340 ft. over NW. slope through old burn with very dense undergrowth and dead and scattered timber.

15.00 Leave old burn, enter heavy timber and dense undergrowth, bears NE. and SW.

18.00 Asc. 70 ft. to

24.90 Spur, slopes W.; desc. 400 ft. over N. slope.

32.00 Creek, 1 lk. wide, course W.; asc. 100 ft. over S. slope.

36.50 Spur, slopes W.; desc. 145 ft. over N. slope.

39.90 Creek, 2 lks. wide, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bed rock, surrounded by a mound of stone, 3 ft. base, 2 ft. high, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S14|S13
1927

from which

A fir, 30 ins. diam., bears N.25*E., 69 lks. dist., marked $\frac{1}{4}$ S 13 B T.

A fir, 18 ins. diam., bears N.55*W., 22 lks. dist., marked $\frac{1}{4}$ S 14 B T.

Asc. 380 ft. over S. slope.

53.00 Spur, slopes W.; desc. 220 ft. over N. slope.

62.15 Creek, 2 lks. wide, course W.; asc. 30 ft. over S. slope.

65.80 Spur, slopes SW.; desc. 75 ft. over NW. slope.

70.40 Creek, 2 lks. wide, course W.; asc. 110 ft. over SE. slope.

74.00 Spur, slopes W.; desc. 30 ft. over NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, with brass cap marked

T25S|R1E
S11|S12

S14|S13
1928

from which

A fir, 24 ins. diam., bears N.26*E., 66 lks.