

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 25 S., R. 1 E.

CHAINS

- 28.20 Creek, 2 lks. wide; course S.; thence along S. slope.
- 38.15 Creek, 5 lks. wide, course S.85*E.; asc. 50 ft. along N. slope.
- 39.95 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
- $\frac{1}{4}$ S1
 S12
 1928
- from which
- A hemlock, 6 ins. diam., bears N.23*E., 32 lks. dist., marked $\frac{1}{4}$ S 1 B T.
- A hemlock, 12 ins. diam., bears S.45*E., 20 lks. dist., marked $\frac{1}{4}$ S 12 B T.
- Asc. 230 ft. over NE. slope.
- 50.60 Spur, slopes N.; desc. 115 ft. over NW. slope.
- 55.60 Brook, 1 lk. wide, course N.; continue desc. along N. slope.
- 59.30 Enter creek, 3 lks. wide, course NE., from W.
- 61.05 Leave creek, comes from NW.
- Ascend 450 ft. over NE. slope.
- 79.90 The cor. of secs. 1, 2, 11 and 12.
- Land, mountainous.
- Soil, rocky loam; 3rd rate.
- Timber, fir, hemlock and cedar.
- Undergrowth, vine maple, rhododendron, hazel and chinquapin.
-
- N.0*01'W., on a true line, bet. secs. 1 and 2.
- Desc. 75 ft. along E. slope, through heavy timber and dense undergrowth.
- 3.80 Creek, 1 lk. wide, course E.; asc. 545 ft. over SE. slope.
- 21.30 Top of spur ridge, bears NE. and SW. Johnson trail, bears same.
- Desc. 400 ft. over NW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in