

Subdivision of T. 25 S., R. 1 E.

CHAINS					
	Soil, rocky; 3rd and 4th rate. Timber, fir, cedar, hemlock and pine. Undergrowth, vine maple, rhododendron and hazel.				
	N.0*02*W., bet. secs. 26 and 27. Desc. 175 ft. over N. slope, through heavy timber and dense undergrowth.				
4.20	Creek, 1 lk. wide, course E.; asc. SE. slope.				
8.00	Thence along E. slope.				
10.20	Desc. 375 ft. to $\frac{1}{4}$ sec. cor., over NE. slope.				
22.00	Continue desc. over N. slope.				
26.00	Desc. gradually over bottom land.				
39.00	Creek, 3 lks. wide, course NW.				
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked				
	$\frac{1}{4}$ <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S27</td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1927</td> <td style="padding: 0 5px;"></td> </tr> </table>	S27	S26	1927	
S27	S26				
1927					
	from which				
	A fir, 16 ins. diam., bears N.14*E., 42 lks. dist., marked $\frac{1}{4}$ S 26 B T.				
	A cedar, 12 ins. diam., bears N.46*W., 13 lks. dist. marked $\frac{1}{4}$ S 27 B T.				
	Desc. gradually, 45 ft. to				
47.20	Steamboat Creek, 110 lks. wide, course S.60*W.; asc. 680 ft. to sec. cor., over S. slope.				
52.60	Top of bluff, 25 ft. high, faces, SE.; continue asc. over SE. slope.				
56.25	Steamboat trail and Forest Service telephone line, bears NE. and SW.				
62.60	Dry ravine, course SE.				
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, with brass cap marked				