

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 25 S., R. 1 E.

CHAINS

- 19.70 Dry ravine, course SW.; asc. 30 ft. over SE. slope.
- 21.80 Spur slopes S.; desc. 345 ft. over W. slope.
- 25.35 Brook, 1 lk. wide, course S.
- 39.91 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S2
 $\frac{1}{4}$ S11
 1928

from which

A cedar, 16 ins. diam., bears S.21 $\frac{1}{2}$ *W., 65 lks. dist., marked $\frac{1}{4}$ S 11 B T.

A fir, 24 ins. diam., bears N.2*W., 39 lks. dist., marked $\frac{1}{4}$ S 2 B T.

Continue desc. over W. slope.

- 50.75 Creek, 10 lks. wide, course S.; asc. NE. slope.

- 67.50 Spur, slopes SE.; desc. SW. slope.

- 79.82 The cor. of secs. 2, 3, 10 and 11.

Land, mountainous.

Soil, rocky loam; 3rd rate.

Timber, fir, hemlock and cedar.

Undergrowth, vine maple, rhododendron, hazel and laurel.

N.0*02'W., on a random line, bet. secs. 2 and 3.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.

- 86.84 Intersect S. bdy. of T. 24 S., R. 1 E., 35 lks. W. of the cor. of secs. 2, 3, 34 and 35, hereinbefore described.

Thence

S.0*12'W., on a true line, bet. secs. 2 and 3.

Desc. 100 ft. over SE. slope, through heavy timber and dense undergrowth.

- 14.70 Thence along broken E. slope.