

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 25 S., R. 1 E.

CHAINS

22, 23, 26 and 27.

Thence

S.89\*48'W., on a true line, bet. secs. 22 and 27.

Asc. SE. slope, through heavy timber and dense undergrowth.

- 1.00 Desc. 20 ft. over SW. slope.
- 4.20 Dry ravine, course S.; asc. 130 ft. over SE. slope.
- 8.60 Spur, slopes S.; desc. 95 ft. over SW. slope.
- 13.60 Dry ravine, course S.; asc. 65 ft. over SE. slope.
- 18.00 Spur, slopes S.; desc. 125 ft. over W. slope.
- 23.70 Creek, 2 lks. wide, course S.; asc. 365 ft. to 1/4 sec. cor. over E. slope.
- 27.70 Dry ravine, course SE.
- 30.70 Dry ravine, course SE.; continue asc. over NE. slope.
- 39.84 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S22}{S27} \\ 1927$$

from which

A fir, 16 ins. diam., bears S.18\*E., 18 lks. dist., marked 1/4 S 27 B T.

A fir, 10 ins. diam., bears N.35\*W., 58 lks. dist., marked 1/4 S 22 B T.

Asc. 80 ft. over E. slope to

- 41.20 Spur, slopes S.; desc. 210 ft. over SW. slope.
- 52.10 Creek, 1 lk. wide, course SW.; asc. 17 ft. over NE. slope.
- 53.10 Spur, slopes S.; desc. 30 ft. over SW. slope.
- 56.50 Creek, 2 lks. wide, course S.; asc. 105 ft. over SE. slope.
- 61.90 Spring branch, 1 lk. wide, course S.
- 67.30 Spur, slopes S.; desc. 60 ft. over SW. slope.