

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 25 S., R. 1 E.

CHAINS	
80.00	<p>A hemlock, 12 ins. diam., for cor. of secs. 15, 16, 21 and 22, I mark</p> <p style="text-align: center;">T 25 S S 15 on NE., R 1 E S 22 on SE., S 21 on SW., and S 16 on NW. side; from which</p> <p>A hemlock, 8 ins. diam., bears N.32*E., 18 lks. dist., marked T 25 S R 1 E S 15 B T.</p> <p>A fir, 20 ins. diam., bears S.18*E., 43 lks. dist., marked T 25 S R 1 E S 22 B T.</p> <p>A hemlock, 14 ins. diam., bears S.63*W., 29 lks. dist., marked T 25 S R 1 E S 21 B T.</p> <p>A hemlock, 8 ins. diam., bears N.23½*W., 56 lks. dist., marked T 25 S R 1 E S 16 B T.</p> <p>Land, mountainous.</p> <p>Soil, coarse rocky loam; 2nd and 3rd rate.</p> <p>Timber, fir, hemlock, cedar and pine.</p> <p>Undergrowth, vine maple, huckleberry, willow, hazel and rhododendron.</p>
40.00	<p>N.89*48'E., on a random line, bet. secs. 15 and 22.</p> <p>Set temp. ¼ sec. cor.</p>
79.98	<p>Intersect N. and S. line, 5 lks. N. of the cor. of secs. 14, 15, 22 and 23.</p> <p>Thence</p> <p>S.89*50'W., on a true line, bet. secs. 15 and 22.</p> <p>Asc. 510 ft. to ¼ sec. cor., over NE. slope.</p>
10.00	<p>Continue asc. along N. slope.</p>
11.20	<p>Creek, 5 lks. wide, course NE.; continue asc. over gradual E. slope.</p>
39.99	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in</p>