

County Surveyor's Record, Douglas County, Oregon

Subdivision of T, 25 S., R. 1 E.

CHAINS

Asc. bare grassy SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bed rock, surrounded by a mound of stone, 4 ft. base, 2 ft. high, for 1/4 sec. cor., with brass cap marked



from which

A pine, 12 ins. diam., bears N.14 1/2 *E., 461 lks. dist., marked 1/4 S 32 B T.

A fir, 6 ins. diam., bears S.18 1/2 *W., 52 lks. dist., marked 1/4 S 31 B T.

Asc. 220 ft. over SE. slope.

43.00 Leave bare grassy slope, enter heavy timber and dense undergrowth, bears NW. and SE.


52.00 Spur, slopes SE.; desc. NE. slope.

59.00 Thence along E. slope.

61.90 Creek, 1 lk. wide, course SE.; asc. 230 ft. over SE. slope.

78.00 Continue asc. over steep S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap marked



from which

A pine, 56 ins. diam., bears N.34 *E., 115 lks. dist., marked T 25 S R 1 E S 29 B T.

A fir, 18 ins. diam., bears S.79 *E., 97 lks. dist., marked T 25 S R 1 E S 32 B T.

A fir, 28 ins. diam., bears S.18 *W., 46 lks. dist., marked T 25 S R 1 E S 31 B T.