

Subdivision of T. 25 S., R. 1 E.

CHAINS	
2.60	Creek, 2 lks. wide, course SE.; continue asc. over gradual E. slope.
14.00	Continue asc. over NE. slope.
29.00	Continue asc. over E. slope.
40.02	Set an iron post, 3 ft. long, 1 in. diam., 27 ins in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S17}{S20}$ 1927
	from which
	A fir, 12 ins. diam., bears S.18*E., 7 lks. dist., marked $\frac{1}{4}$ S 20 B T.
	A fir, 8 ins. diam., bears N.63*W., 54 lks. dist., marked $\frac{1}{4}$ S 17 B T.
	Asc. 190 ft. over E. slope to
50.00	Top of spur ridge, bears N. and S.; desc. 1060 ft. to sec. cor. over steep rocky SW. slope, through bluffs.
65.80	Top of bluff, 30 ft. high, faces W.
80.04	The cor. of secs. 17, 18, 19 and 20.
	Land, mountainous.
	Soil, rocky loam; 3rd and 4th rate.
	Timber, fir, hemlock, pine, cedar and madrona.
	Undergrowth, vine maple, rhododendron, laurel, hazel, snow brush and manzanita.
	West, on a true line, bet. secs. 18 and 19.
	Desc. 460 ft. over SW. slope, through heavy timber and dense undergrowth.
5.75	Spur, slopes SW.; continue desc. over W. slope.
12.75	Creek, 4 lks. wide, course S.20*W.; asc. 225 ft. over E. slope.