

Subdivision of T. 25 S., R. 1 E.

CHAINS

Asc. 85 ft. over SW. slope, through heavy timber and dense undergrowth.

2.70 Spur, slopes SW.; desc. 50 ft. over NW. slope.

8.00 Thence along broken W. slope.

13.00 Asc. 180 ft. over SW. slope.

20.00 Spur, slopes W.; desc. 125 ft. over NW. slope.

27.00 Dry ravine, course SW.; asc. 70 ft. over S. slope.

29.15 Spur, slopes W.; desc. 55 ft. over NW. slope.

35.15 Creek, 3 lks. wide, course SW.; asc. 150 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S18 | S17  
1927

from which

A fir, 18 ins. diam., bears N.69\*E., 119 lks. dist., marked  $\frac{1}{4}$  S 17 B T.

A fir, 15 ins. diam., bears S.85\*W., 66 lks. dist., marked  $\frac{1}{4}$  S 18 B T.

Asc. 980 ft. to sec. cor. over steep and rocky S. slope.

46.00 Spur, slopes SE.; continue asc. along rocky E. slope.

54.00 Rocky spur, slopes SW.; continue asc. over SW. slope.

60.20 Brook, 1 lk. wide, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap marked

T25S | R1E  
S7 | S8  
-----  
S18 | S17  
1927

from which

A fir, 24 ins. diam., bears N.74\*E., 38 lks. dist., marked T 25 S R 1 E S 8 B T.