

County Surveyor's Record, ¹²⁴Douglas County, Oregon

Subdivision of T. 25 S., R. 1 E.

CHAINS	
	from which
	A pine, 12 ins. diam., bears N.36*E., 18 lks. dist., marked $\frac{1}{4}$ S 5 B T.
	A fir, 30 ins. diam., bears S.27*E., 10 lks. dist., marked $\frac{1}{4}$ S 8 B T.
	Continue to ascend along N. slope.
48.00	Spur, slopes S.75*E.; thence along S. slope.
80.20	The cor. of secs. 5, 6, 7 and 8.
	Land, mountainous.
	Soil, rocky loam; 3rd and 4th rate.
	Timber, fir, hemlock, cedar, pine and spruce.
	Undergrowth, vine maple, rhododendron and hazel.
	West, on a true line, bet. secs. 6 and 7.
	Asc. 120 ft. over SE. slope, through heavy timber and dense undergrowth.
12.00	Thence along S. slope.
21.00	Dry ravine, course SE.; continue asc. over SE. slope.
32.00	Top of spur ridge, bears N. and S., slopes S.; desc. 175 ft. over SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{\frac{1}{4} \text{ S6}}{\text{S7}}$ 1927
	from which
	A fir, 48 ins. diam., bears S.30*E., 42 lks. dist., marked $\frac{1}{4}$ S 7 B T.
	A fir, 18 ins. diam., bears N.18*W., 54 lks. dist., marked $\frac{1}{4}$ S 6 B T.
	Desc. 45 ft. over SW. slope.
41.50	Dry ravine, course SW.; thence along S. slope.
45.50	Desc. 245 ft. over SW. slope.