

County Surveyor's Record, Douglas County, Oregon

Retracement of the S. Bdy. of T. 25 S., R. 1 E.

CHAINS

The E. half of this line is West., 39.98 chs. and the
W. half is West., 37.32 chs.

RESURVEY OF THE S. BDY. OF T. 25 S., R. 1 E.

From the $\frac{1}{2}$ sec. cor. of sec. 36 only, which is an iron
post, 1 in. in diam., protruding 9 ins. above ground,
with brass cap marked.

 $\frac{1}{2}$ S 36

1927

From which the original bearing trees,

A fir, 12 ins. in diam., bears N.34*E., 38 lks.

dist., marked $\frac{1}{2}$ S 36 B T

A fir, 22 ins. in diam., bears N.77*W., 40 lks.

dist., marked $\frac{1}{2}$ S 36 B T

Thence,

West, on a true line on the W. $\frac{1}{2}$ of the S. bdy. of sec. 36.

Desc. 250 ft. over SW. slope, through timber and brush.

7.85 Deep Creek, 5 lks. wide, course NW.

Asc. 400 ft. over NE. slope.

21.17 Point for the closing Tp. cor. of T. 25 $\frac{1}{2}$ S., Rs. 1 & 2
E., later determined and hereinafter described.

22.50 Spur, slopes N.; desc. 340 ft. over N. slope.

28.00 Bluff, 40 ft. high, faces W.

33.50 Creek, 5 lks. wide, course N.

39.25 Creek, 1 lk. wide, course NE.

40.00 Intersect the cor. of secs. 35 and 36 only, which is an
iron post, 2 ins. in diam., protruding 9 ins. above
ground, with brass cap marked.T25SR1E
S35 S36

1927

From which the original bearing trees,