

## County Surveyor's Record, Douglas County, Oregon

Resurvey of the S. bdy. of T. 25 S., R. 1 E.

## CHAINS

- 12.00 Spur, slopes NE.; desc. 340 ft. over NW. slope.
- 15.85 Bluff, 75 ft. high, faces W.
- 21.45 Point for the  $\frac{1}{4}$  sec. cor. of sec. 35 only, later determined.  
Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. with brass cap mkd.
- $\frac{1}{4}$  S 35  
1928
- From which
- A fir, 8 ins. in diam., bears S.60\*E., 21 lks.  
dist., mkd.  $\frac{1}{4}$  S 35 B T
- A fir, 9 ins. in diam., bears S.12\*W., 10 lks.  
dist., mkd.  $\frac{1}{4}$  S 35 B T
- 23.60 Bluff, 50 ft. high, faces SW.
- 24.50 Dry ravine, course NW.; asc. 45 ft. over rocky NE. slope.
- 31.25 Spur, slopes N.; desc. 205 ft. over NW. slope.
- 37.25 Dry ravine, course NW.; asc. 60 ft. over NE. slope.
- 40.04 Intersect the  $\frac{1}{4}$  sec. cor. of sec. 34 only, which is an iron post, 1 in. in diam., protruding 9 ins. above ground, with brass cap mkd.
- $\frac{1}{4}$  S 34  
1927
- From which the original bearing trees,
- A fir, 16 ins. in diam., bears N.48\*E., 33 lks.  
dist., mkd.  $\frac{1}{4}$  S 34 B T
- A fir, 36 ins. in diam., bears N.17\*W., 10 lks.  
dist., mkd.  $\frac{1}{4}$  S 34 B T
- 40.25 Top of rocky point, slopes NW., and top of bluff, 50 ft. high, faces W.  
Desc. 165 ft. over W. slope to
- 46.00 Creek, 2 lks. wide, course N.; asc. 100 ft. over NE. slope.
- 49.75 A small lake,  $1\frac{1}{2}$  chs. in diam., bears S., 1 ch. dist.
- 57.35 Spur, slopes N.; descend 415 ft. over NW. slope.
- 61.54 Point for the closing cor. of secs. 34 and 35, later determined and hereinafter described.