

## County Surveyor's Record, Douglas County, Oregon

Resurvey of the S. bdy. of T. 25 S., R. 1 E.

CHAINS

A fir, 8 ins. in diam., bears S.15\*W., 30 lks.  
dist., mkd.  $\frac{1}{4}$  S 34 B T

37.25 Dry ravine, course SW.; continue descent along S. slope.

39.92 Intersect the  $\frac{1}{4}$  sec. cor. of sec. 33 only, which is an  
iron post, 1 in. in diam., protruding 9 ins. above  
ground, with brass cap mkd.

$\frac{1}{4}$  S33  
1927

From which, the original bearing trees,

A fir, 38 ins. in diam., bears N.34\*E., 64 lks.  
dist., mkd.  $\frac{1}{4}$  S 33 B T

A fir, 18 ins. in diam., bears N.65\*W., 44 lks.  
dist., mkd.  $\frac{1}{4}$  S 33 B T

Desc. 320 ft. over SW. slope.

47.35 Creek, 1 lk. wide, course N W.; continue desc. over NW.  
slope.

56.80 Creek, 1 lk. wide, course N.; asc. 40 ft. over E. slope.

58.50 Spur, slopes N.; desc. 15 ft. to

59.25 Asc. 185 ft. over broken N. slope.

61.65 Point for the closing cor. of secs. 33 and 34 later de-  
termined and hereinafter described.

65.60 Brook, 1 lk. wide, course N.; continue asc. over NE. slope.

78.35 Spur, slopes N.; descend 50 ft. over NW. slope.

80.04 Intersect the cor. of secs. 32 and 33 only, which is an  
iron post, 2 ins. in diam., protruding 9 ins. above  
ground, with brass cap mkd.

T25SR1E  
S32 | S33  
1927

From which the original bearing trees,

A fir, 6 ins. in diam., bears N.25\*E., 13 lks.  
dist., mkd. T 25 S R 1 E S 33 B T

A fir, 6 ins. in diam., bears N.33\*W., 16 lks.  
dist., mkd. T 25 S R 1 E S 32 B T

Land, mountainous.

Soil, coarse rocky loam; 2nd and 3rd rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, vinemaple, rhododendron, hazel &amp; huckleberry.