

County Surveyor's Record, Douglas County, Oregon

Resurvey of the S. bdy. of T. 25 S., R. 1 E.

CHAINS

West, on a true line on the S. bdy. of sec. 32.
 Desc. 175 ft. over NW. slope, through heavy timber and
 dense undergrowth.

2.74 Bluff, 40 ft. high, faces NW.

8.75 Dry ravine, course N.; asc. 60 ft. over NE. slope.

11.60 Spur, slopes NW.; desc. 370 ft. over W. slope.

21.75 Point for the $\frac{1}{4}$ sec. cor. of sec. 33 only, later de-
 termined.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
 the ground, for the $\frac{1}{4}$ sec. cor. of sec. 33 only, with
 brass cap mkd.

$\frac{1}{4}$ S33
1928

From which,
 A cedar, 14 ins. in diam., bears S.5*E., 104 lks.
 dist., mkd. $\frac{1}{4}$ S 33 B T
 A cedar, 14 ins. in diam., bears S.45*W., 73 lks.
 dist., mkd. $\frac{1}{4}$ S 33 B T

22.40 Creek, 2 lks. wide, course N.; asc. 475 ft. over NE. slope.
 34.35 Spur, slopes N.; desc. 95 ft. over W. slope.
 39.00 Dry ravine, course N W.
 40.06 Intersect the $\frac{1}{4}$ sec. cor. of sec. 32 only, which is an
 iron post, 1 in. in diam., protruding 9 ins. above
 ground, with brass cap mkd.

$\frac{1}{4}$ S32
1927

From which the original bearing trees,
 A hemlock, 15 ins. in diam., bears N.71*E., 26 lks.
 dist., mkd. $\frac{1}{4}$ S 32 B T
 A hemlock, 10 ins. in diam., bears N.42*E., 75 lks.
 dist., mkd. $\frac{1}{4}$ S 32 B T

Asc. 130 ft. over NE. slope.

45.20 Spur, slopes NW.; desc. 280 ft. over W. slope.

54.25 Dry ravine, course NW.; asc. 195 ft. over NE. slope.

61.65 Spur, slopes NW.; desc. 370 ft. over W. slope.

61.90 Point for the closing cor. of secs. 32 and 33, later
 determined and hereinafter described.

77.30 Creek, 1 lk. wide, course NE.; asc. 50 ft. over E. slope.

79.25 Spur, slopes N.

80.02 Intersect the cor. of secs. 31 and 32 only, which is an
 iron post, 2 ins. in diam., protruding 9 ins. above