

County Surveyor's Record, Douglas County, Oregon

Resurvey of the S. bdy. of T. 25 S., R. 1 E.

CHAINS

- 35.00 Canton Creek trail and Forest Service telephone line,
bear NE. and SW.
- 39.98 Intersect the $\frac{1}{4}$ sec. cor. of sec. 31 only, which is an
iron post, 1 in. in diam., protruding 9 ins. above
ground with brass cap mkd.
- $\frac{1}{4}$ S31
1927
- From which the original bearing trees,
- A fir, 8 ins. in diam., bears N.25*E., 96 lks.
dist., mkd. $\frac{1}{4}$ S 31 B T
- A fir, 6 ins. in diam., bears N.75*W., 21 lks.
dist., mkd. $\frac{1}{4}$ S 31 B T
- 42.00 Spur, slopes S.; desc. 45 ft. over SW. slope.
- 44.80 Canton Creek trail and Forest Service telephone line,
bears NW. and SE.
- 45.95 Canton Creek, 100 lks. wide, course SE.; asc. 680 ft.
over NE. slope.
- 61.97 Point for the closing cor. of secs. 31 and 32, later de-
termined and hereinafter described.
- 76.85 Dry ravine, course N E.
- 77.30 Intersect the cor. of Tps. 25 S., Rs. 1 E. and 1 W.,
which is a basalt stone 12x8x5 ins. above ground,
mkd.

25S on N.,
1E. on E., and
1W. on W. face

- From which the following original bearing trees,
- A fir, 8 ins. in diam., bears N.67 $\frac{1}{2}$ *E., 86 lks.
dist., mkd. T 25 S R 1 E S 31 B T
- A fir, 30 ins. diam., bears N.54 $\frac{1}{2}$ *W., 80 lks.
dist., mkd. T 25 S R 1 W S 36 B T
- Land; mountainous.
- Soil; coarse rocky loam, 2nd and 3rd rates.