

County Surveyor's Record, Douglas County, Oregon

Resurvey of the S. bdy. of sec. 36, T. 25 S., R. 1 W.

CHAINS

A cedar, 5 ins. diam., bears S.55*E., 16 lks.

dist., mkd. $\frac{1}{4}$ S 31 B T

A fir, 20 ins. diam., bears S.23*W., 56 lks.

dist., mkd. $\frac{1}{4}$ S 31 B T

40.64 Intersect the $\frac{1}{4}$ sec. cor. established for secs. 1 and 36 which is a squared fir stake, 3x3x18 ins. above ground, badly decayed, no marks legible.

This cor. will hereafter refer to sec. 36 only, destroy scribe marks on old SW. bearing tree.

In place of old cor. stake;

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd.

$\frac{1}{4}$ S36

1928

From which,

A fir, snag, 14 ins. diam., bears N.86*E., 158 lks.

(not S.86*E., 162 lks.) dist., mkd. $\frac{1}{4}$ S 36 B T(not $\frac{1}{4}$ S 1 B T) old bearing tree.

A fir, 30 ins. diam., bears S.87*W., 159 lks. (not

N.87*W., 195 lks.) dist., mkd. $\frac{1}{4}$ S 1 B T (not $\frac{1}{4}$ S 36 B T.) old bearing tree.

A fir, 18 ins. diam., bears N.26*E., 52 lks.

dist., mkd. $\frac{1}{4}$ S 36 B T

A fir, 10 ins. diam., bears N.63*W., 81 lks.

dist., mkd. $\frac{1}{4}$ S 36 B T.

Thence,

N.89*45*W.,

2.00 Spur, slopes S.; desc. 185 ft. over broken SW. slope.

9.20 Spring branch, 1 lk. wide, course S., asc. 50 ft. along broken S. slope.

17.25 Intersect the closing Tp. cor. of Tps. 25 $\frac{1}{2}$ and 26 S., Rs. 1 E., and 1 W., as described in the notes of T. 26 S., R. 1 E., desc. 30 ft. along S. slope.