

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 25 $\frac{1}{2}$ S., R. 1 E.

CHAINS

A hemlock, 10 ins. in diam., bears S.30*E., 41 lks.

dist., mkd. T 25 $\frac{1}{2}$ S R 1 E S 36 C C B T

A hemlock, 12 ins. in diam., bears S.36*W., 46 lks.

dist., mkd. T 25 $\frac{1}{2}$ S R 1 E S 35 C C B T

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, hemlock, cedar and yew.

Undergrowth, vinemaple and rhododendron.

From the cor. of secs. 2,3,34 and 35 on the S. bdy. of the Tp., as described in the notes of T. 26 S., R. 1 E.

Thence,

N.0*02W., bet. secs. 34 and 35

Asc. 70 ft. over S., slope, through timber and brush.

4.00 Divide bet. Steamboat Creek and the N. Umpqua River, bears E. and W.: Desc. 670 ft. over N. slope.

18.80 Enter creek, 1 lk. wide, course N. from the SE.

22.50 Leave same creek, course NW.

26.00 Draw, course NW.; asc. 45 ft. over S. slope.

28.30 Small spur, slopes N.55*W.; desc. 50 ft. over NW. slope.

30.00 Small draw, course NW.; asc. 30 ft. over S. slope.

34.60 Intersect the N. bdy. of the Tp., 18.40 chs. E. of the cor. of secs. 33 and 34 only, as hereinbefore described

At point of intersection;

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 34 and 35, with brass cap mkd.

T25SR1E

S34

S34 | S35

T25 $\frac{1}{2}$ SR1E

C C

1928

From which,