

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 25½ S., R. 1 E.

CHAINS

A fir, 20 ins. in diam., bears S.50\*E., 65 lks.

dist., mkd. T 25½ S R 1 E S 35 C C B T

A fir, 18 ins. in diam., bears S.22\*W., 105 lks.

dist., mkd. T 25½ S R 1 E S 34 C C B T

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, vinemaple and service berry.

From the cor. of secs. 3, 4, 33 and 34 on the S. bdy.  
of the Tp., as described in the notes of T. 26 S.,  
R. 1 E.

Thence,

N.0\*02'W., bet. secs. 33 and 34.

Asc. 300 ft. over broken S. slope, through timber and  
brush.

16.00 Divide bet. Steamboat Creek and the North Umpqua  
River bears E. and W.; desc. 580 ft. over broken N.  
slope.

25.50 Spring, 30 lks. E. of line, course NE.

34.76 Intersect the N. bdy. of the Tp., 18.39 chs. E. of the  
cor. of secs. 32 and 33 only, as hereinbefore de-  
scribed.

At point of intersection;

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins.  
in the ground, for the closing cor. of secs. 33 & 34,  
with brass cap mkd.

T25SR1E  
S33  
-----  
S33|S34  
T25½SR1E  
C C  
1928

From which,