

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 25 $\frac{1}{2}$ S., R. 1 E.

CHAINS

A cedar, 10 ins. in diam., bears S.10*E., 75 lks.
dist., mkd. T 25 $\frac{1}{2}$ S R 1 E S 34 C C B T

A hemlock, 16 ins. in diam., bears S.16*W., 50 lks.
dist., mkd. T 25 $\frac{1}{2}$ S R 1 E S 33 C C B T

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, vinemaple and rhododendron.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of
the Tp., as described in the notes of T. 26 S., R. 1 E.

Thence,

N.0*03W., bet. secs. 32 and 33.

Asc. 500 ft. over broken S. slope, through timber and
brush.

7.20 Small spur, slopes S.20*W.

18.00 Forest Service telephone line, bears N.75*E. and S.75*W.

18.70 Divide, bet. Steamboat Creek and the North Umpqua River,
bears E. and W.; desc. 410 ft. over broken N. slope.

34.10 Spur, slopes N.20*W.

34.90 Intersect the N. bdy. of the Tp., 18.12 chs. E. of the
cor. of secs. 31 and 32 only, hereinbefore described.

At point of intersection;

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins.
in the ground, for the closing cor. of secs. 32 & 33,
with brass cap mkd.

T25SR1E
S32
S32 | S33
T25 $\frac{1}{2}$ SR1E
C C
1928

From which,

A fir, 16 ins. in diam., bears S.60*E., 17 lks.
dist., mkd. T 25 $\frac{1}{2}$ S R 1 E S 33 C C B T