

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 25½ S., R. 1 E.

CHAINS

A fir, 12 ins. in diam., bears S.30\*W., 18 lks.  
dist., mkd. T 25½ S R 1 E S 32 C C B T

Land, mountainous.

Soil, rocky loam, 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, vine maple and service berry.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy.  
of the Tp., as described in the notes of T. 26 S., R.  
1 E.

Thence,

N.0\*04'W., bet. secs. 31 and 32.

Desc. 70 ft. over N. slope, through timber and brush.

7.50 North Umpqua River, 180 lks. wide, course S.80\*W., at  
the mouth of Steamboat Creek, from the NE.; asc. 620  
ft. over S. slope.

11.00 Steamboat road, bears E. and W.

11.76 SW. corner of Steamboat house (9x12 ft.) bears E. 25 lks.  
dist.

27.95 Rock Creek and Steamboat Bridge Trail, bears E. and W.,  
on spur, slopes E.; desc. 200 ft. over NE. slope.

35.00 Intersect the N. bdy. of the Tp., 15.33 chs. E. of the  
cor. of Tps. 25 S., Rs. 1 W. and 1 E., as herein-  
before described.

At point of intersection;

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in  
the ground, for the closing cor. of secs. 31 and 32,  
with brass cap mkd.

T25SR1E  
S31  
-----  
S31 S32  
T25½SR1E  
C C  
1928

From which,