

South Boundary of T. 24 South, Range 2 E.,  
 As surveyed by John G. Collins, U. S. Cadastral Engineer,  
 Under Special Instructions dated March 12th, 1921.

CHAINS

See Pages 9247 A + B for NE Tsp corner T25S R2E and NW Tsp corner T25S R3E

- From the cor. of Tps. 24 and 25 S., R. 2 E. only,  
 West, on a True line bet. Secs. 1 and 36.  
 Descend 860 ft. over SW slope to  $\frac{1}{4}$  Sec. cor., through  
 heavy timber and dense undergrowth.
- 17.54 Spring branch, 4 lks. wide, course SW.  
 20.27 Spring branch, 3 lks. wide, course SW.  
 24.60 Spring branch, 2 lks. wide, course SW.  
 26.20 Spring branch, 3 lks. wide, course SW.  
 34.00 Creek, 6 lks. wide, course NW; continue descent along  
 N and NW slope.  
 38.80 Enter same creek, comes from NE; flows W., 10 lks. wide.  
 40.00 The point for the  $\frac{1}{4}$  Sec. cor. falls on bed rock bottom  
 of creek.  
 42.00 Leave creek, flows NW.  
 42.84 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
 the ground, for witness cor. to the  $\frac{1}{4}$  Sec. cor., with  
 brass cap marked

S36  
 $\frac{1}{4}$  WC  
 S1  
 1926

from which

A Cedar, 6 ins. diam., bears N.35\*E., 43 lks.  
 dist., marked W C  $\frac{1}{4}$  S 36 B T.

A Fir, 6 ins. diam., bears S.76\*E., 56 lks.  
 dist., marked W C  $\frac{1}{4}$  S 1 B T.

Descend along N slope.

- 48.75 Enter same creek, comes from NE., flows W. 10 lks. wide.  
 52.00 Leave creek, flows SW; thence along S slope.  
 75.35 Spur, slopes S., descend 180 ft. over W slope.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
 the ground, for cor. of Secs. 1, 2, 35 and 36, with  
 brass cap marked

T24S R2E  
 S35 S36

S2 S1  
 T25S  
 1926