

East Boundary of T. 24 R., R. 2 E.

Chains.

30.20 Leave vine, maple thicket, enter heavy timber and dense undergrowth, bears E. and W.

34.25 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 31 only, with brass cap marked

1/4 S31
 1926

from which

A fir, 8 ins. diam., bears N.55°E., 35 lks. dist., marked 1/4 S 31 B T.

A fir, 8 ins. diam., bears S.59°E., 65 lks. dist., marked 1/4 S 31 B T.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 36 only, with brass cap marked

1/4 S36
 1926

from which

A fir, 10 ins. diam., bears S.25°W., 45 lks. dist., marked 1/4 S 36 B T.

A fir, 10 ins. diam., bears N.44°W., 63 lks. dist., marked 1/4 S 36 B T.

Continue asc. along W. slope.

63.00 Spur, slopes NW.; desc. 450 ft. over SW. slope.

74.25 Point of intersection of S. bdy. of T. 24 S., R. 3 E., determined as hereafter set forth in the notes of T. 24 S., R. 3 E., in Book "B", under this Group.
 Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, for closing cor. of Tps. 24 and 25 S., R. 3 E., with brass cap marked

T24S | T24S
 | R3E
 | S31
 R2E | CC
 | S6
 S36 | T25S
 1926

from which