

Subdivisions of T. 25 S., R. 2 E.

CHAINS

From the cor. of secs. 35 and 36 only, on S. bdy of Tp. N.0*01'W., bet. secs. 35 and 36

Asc. 280 ft. over S. slope, through heavy timber and dense undergrowth.

8.10 Ridge, bears NW. and SE., way trail along top of ridge, desc. 638 ft. over broken NE. slope

13.00 Spur, slopes NE.

22.00 Spring, course NE.

30.00 Spur, slopes NE.


36.00 Draw, course NE.

40.00 Point for 1/4 sec. cor. falls on steep insecure ground, impracticable to set cor.

Desc. 146 ft. over N. slope.

42.50 Creek, 2 lks. wide, course E., asc. 245 ft. over S. slope

49.50 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. to the 1/4 sec. cor. of secs. 35 and 36, with brass cap marked



from which,

A fir, 28 ins. diam., bears S.45*E., 31 lks. dist., marked W C 1/4 S 36 B T

A hemlock, 38 ins. diam., bears S86*W., 32 lks. dist., marked W C 1/4 S 35 B T

Asc. 720 ft. over SE., changing to S. slope.

74.20 Spur, slopes SE., desc. 82 ft. over NE. slope.

79.88 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for witness cor. to the cor. of secs. 25, 26, 35, and 36, with brass cap marked

