


Subdivisions of T. 25 S., R. 2 E.

CHAINS

- 15.00 Draw, course S.80*W.,
- 22.50 Draw, course NW., asc. 83 ft. over SW. slope.
- 30.90 Spur, slopes W., desc. 15 ft. over NW. slope.
- 32. 10 Draw, course SW., asc. 258 ft. over S. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, with brass cap marked.




from which,

A fir, 26 ins. diam., bears S.63*E., 18 lks. dist., marked $\frac{1}{4}$ S 24 B T

A fir, 26 ins. diam., bears S. 86*W., 58 lks. dist., marked $\frac{1}{4}$ S 23 B T

Asc. 110 ft. over S. slope.

- 43.30 Spur, slopes SW., asc. 64 ft. along SW. slope.
- 53.20 Spur, slopes W., desc. 816 ft. over NW. slope.
- 74.20 Creek, 4 lks. wide, course W.,
- 75.00 Reynolds Creek, 6 lks. wide, course SW., asc. 196 ft. over SW. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the cor. of secs. 13, 14, 23, and 24 with brass cap marked



from which,

A fir, 20 ins. diam., bears N.78*E., 39 lks. dist., marked T 25 S R 2 E S 13 B T

A fir, 10 ins. diam., bears S.24*E., 37 lks. dist., marked T 25 S R 2 E S 24 B T

A fir, 12 ins. diam., bears S.86*W., 12 lks. dist., marked T 25 S R 2 E S 23 B T