

Subdivisions of T. 25 S., R. 2 E.

CHAINS

N.0*02'W., bet. secs. 22 and 23

Desc. 356 ft. along gradual NW. slope, to $\frac{1}{4}$ sec. cor.,
through heavy timber and dense undergrowth.

13.50 Spur, slopes W.,

22.30 Spur, slopes W.,

35.00 Creek, 2 lks. wide, course NW.,

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23,
with brass cap marked

$\frac{1}{4}$
S22 | S23
1928

from which,

A fir, 24 ins. diam., bears S.66*E., 47 lks.
dist., marked $\frac{1}{4}$ S 23 B T

A fir, 14 ins. diam., bears N.31*W., 12 lks.
dist., marked $\frac{1}{4}$ S 22 B T

Desc. 75 ft. along broken gradual W. slope.

54.60 Creek, 1 lk. wide, course NW.

56.60 Creek, 3 lks. wide, course NW.,

60.20 Spur, slopes W.,

64.00 Reynolds Creek, 12 lks. wide, course W., asc. 137 ft.
over SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for the cor. of secs. 14, 15, 22, and 23
with brass cap marked

T25S | R2E
S15 | S14

S22 | S23
1928

from which,

A cedar, 14 ins. diam., bears N.75*E., 64 lks.
dist., marked T 25 S R 2 E S 14 B T

A yew, 4 ins. diam., bears S.74*E., 37 lks.
dist., marked T 25 S R 2 E S 23 B T